





Torque Dampers - Compact uni-directional - 120° operating angle

Torque Dampers



Q0440

TORQUE DAMPERS

Material

Body: stainless steel, AISI 304. Shaft: PBT plastic. White for anti-clockwise version, grey for clockwise version. Different torque forces marked by colour coded dot on shaft.

Technical Notes

120° operating angle, additional 5° dead

angle at start/end position.
Tested to over 100,000 cycles.
Temperature range 0° to 40°C.

Tips


Provide smooth and quiet motion of lids, covers etc. Ideal for special purpose machines, air conditioning units etc.

Important Notes

Torque calculation:

$T \text{ (Kgf.cm)} = W \text{ (Kg)} \times 0.5 \times H \text{ (cm)}$.
W (Kg) is weight of cover/lid, H (cm) is distance between fulcrum and cover/lid's opening edge.

Order No.	Type	Shaft colour	Operating angle	Torque colour marking	Torque Ncm	Weight g
Q0440.AC0010	Anti-Clockwise	White	120°	Blue	8,2 - 15,3	10
Q0440.AC0020	Anti-Clockwise	White	120°	Red	15,3 - 25,5	10
Q0440.AC0110	Clockwise	Grey	120°	Blue	8,2 - 15,3	10
Q0440.AC0120	Clockwise	Grey	120°	Red	15,3 - 25,5	10





Wixroyd torque dampers offer controlled opening and closing of lids, drawers, covers and much more, they provide a wide range of solutions for a variety of applications creating smooth movement and function.

Though unnoticed in many applications, torque dampers are a vital part of many products bringing quality, safety and durability. Torque dampers provide quality movement enhancing both touch and feel.


Operating principle

Torque dampers utilise the movement of fluid forced from one chamber to another via a rotor. Dampening speed is dependent upon the viscosity of the fluid and the diameter of the fluid aperture.

Torque calculation







To calculate the torque for your application, the following measurements are necessary.

t (torque) = $w \times 0.5 \times h$
 h = length from pivot point to end of lid (cm)
 w = weight of the lid (Kg)



Torque force stated per product (see individual product pages), is the maximum torque to which the specified part can be exposed before the dampening force yields and hence dampening is overcome.

Table of torque dampers: Torque ranges

Part no.	Torque damper range	Torque Kgf.cm	Torque Kgf.cm														
			10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
	Q0400 Starting position (Dead angle) 5° Ending position (Dead angle) 115° 5°	15 - 35	[Bar from 20 to 35]														
	Q0420 Starting position (Dead angle) 5° Ending position (Dead angle) 120° 5°	10 - 25	[Bar from 10 to 25]														
	Q0422 Starting position (Dead angle) 5° Ending position (Dead angle) 110° 5°	10 - 35	[Bar from 10 to 35]														
	Q0430 Starting position (Dead angle) 5° Ending position (Dead angle) 125° 5°	20 - 30	[Bar from 20 to 30]														
	Q0440 Starting position (Dead angle) 5° Ending position (Dead angle) 120° 5°	8 - 25	[Bar from 10 to 25]														
	Q0460 Starting position (Dead angle) 5° Ending position (Dead angle) 110° 5°	10 - 18	[Bar from 10 to 18]														
	Q0462 Starting position (Dead angle) 5° Ending position (Dead angle) 110° 5°	10 - 30	[Bar from 10 to 30]														
	Q1000 Starting position (Dead angle) 5° Ending position (Dead angle) 115° 5°	30 - 70	[Bar from 30 to 70]														
	Q1002 Starting position (Dead angle) 5° Ending position (Dead angle) 115° 5°	60 - 140	[Bar from 60 to 140]														
	Q1010 Starting position (Dead angle) 5° Ending position (Dead angle) 120° 5°	30 - 50	[Bar from 30 to 50]														
	Q1050 Starting position (Dead angle) 5° Ending position (Dead angle) 120° 5°	20 - 50	[Bar from 20 to 50]														
	Q1060 Starting position (Dead angle) 5° Ending position (Dead angle) 120° 5°	61 - 81	[Bar from 61 to 81]														